



PIPE BENDERS



PART NUMBER	DESCRIPTION
42TB130	TB130 Top Bender

Min. Outside Diameter	1/4"
Max. Outside Diameter	5"
Pip Capacity (Max.)	4" Sch. 40
Minimum CLR	2D *Depending on Material & Wall Thickness
Maximum CLR	27.5"
Angle Range	0-210 Degrees
Bending Speed	Variable to .75 RPM
Programing	Touch Screen, Unlimited Storage with USB
Two Axis Positioner	Yes *Consult w/ Rep
Voltage Requirement	220 or 440V 3ph
Motor	3.5 horsepower @ 480V
Dimensions	34" L, 34" W, 47" H
Shipping Weight	1330 Lbs



PART NUMBER	DESCRIPTION
42MB42B	MB42B Bench Top

Min. Outside Diameter	1/4"
Max. Outside Diameter	1-1/2"
Pip Capacity (Max.)	1" Sch. 40
Minimum CLR	2D *Depending on Material & Wall Thickness
Maximum CLR	7-1/2"
Angle Range	0-210 Degrees
Bending Speed	2 RPM
Programing	NC w/ Touchpad, 30 Individual Programs w/ 9 Bends Each
Two Axis Positioner	No
Voltage Requirement	120V *220V 3ph Available
Motor	2 hp 50-60 Hz
Dimensions	25" L, 15" W, 21" H
Shipping Weight	197 Lbs



Additional Models and Accessories Available!!



Don't see what you are looking for.....

Contact your Rayco Rep for more information regarding the products in this category!!

Phone: 757-431-0698 Fax: 757-431-2634
Rayco@RaycoSupply.com www.RaycoSupply.com